

Integro Surgical Products

Blanket and Fluid Warming Cabinets



Warming Cabinets

Data logging warming cabinets provide independent, digitally controlled heating chambers that offer actual temperature and set point displays. Data is recorded every 30 minutes and stored for up to two years. Choose from single and dual chamber units.



Standard Features

- “Easy Log” integrated data logger with removable USB
- Keyed temperature lock out
- Adjustable feet
- Stainless steel doors
- Automatically records data every 30 minutes
- Internal storage up to 2 years
- Displays actual temperature and set points at all times
- Independent digitally controlled heating chambers
- Rapid warm time (2-6 hours depending on load)
- Push button digital operation
- Large digital display(s)
- Fully insulated to provide uniform heating
- Audible & visual over-temperature alarm

Optional Features

- Full view glass door
- Left or right hand door hinge
- Celsius (SMWCCELSIUS)
- Recessed unit option
- Seismic braces (SMWC24SB for 24" w cabinets; SMWC36SB for 36" w cabinets)

Operating Instructions

1. Power system by pressing power switch to the ON position
2. To change the set point, press arrow keys up or down
Press SET when at new set point
3. Press ALARM RESET to silence the alarm

Sample Report

Date/Time	Temperature	°C/°F
10/10/2018 23:12	106	°F
10/10/2018 23:43	106	°F
10/11/2018 0:12	106	°F
10/11/2018 0:43	106	°F
10/11/2018 1:12	106	°F

To Download Data

1. Insert supplied USB flash drive into USB slot
2. Data download will begin automatically
3. During download display will read:



4. Once the display shows the temperature again, it is safe to remove the flash drive
5. Data is saved on the flash drive as a .CSV file for easy import into most spreadsheet programs such as Excel
6. Data is secure (no reporting or connection to any network)

Single Chamber Units

Product Number	Door Type	Base Type	Dimensions
SM202424SWCGRNB	Right-hinged glass	No base	24"w x 20.5"d x 24.5"h
SM202424SWCGLNB	Left-hinged glass		
SM202424SWCSRNB	Right-hinged solid		
SM202424SWCSLNB	Left-hinged solid		
SM202858SWCGRM	Right-hinged glass	Mobile stand	28"w x 20"d x 58.75"h
SM202858SWCGLM	Left-hinged glass		
SM202858SWCSR	Right-hinged solid		
SM202858SWCSLM	Left-hinged solid		
SM202424SWCGRNBR	Right-hinged glass	Recessed (includes trim kit)	24"w x 20.5"d x 24.5"h
SM202424SWCGLNBR	Left-hinged glass		
SM202424SWCSRNB	Right-hinged solid		
SM202424SWCSLNB	Left-hinged solid		

Chamber I.D.

20"w x 17"d x 15.25"h
 3.0 Cubic Feet Storage
 Temperature Range
 90°-160° F (Tolerance +/- 1° F)

Electrical

120V, 2.9 Amp, 50/60 Hz,
 .23 kWh (Avg.),
 785 BTU/hr (Avg.)



SM202424SWCGRNB
 No base (NB) standard for this model

Product Number	Door Type	Base Type	Dimensions
SM263024SWCGRNB	Right-hinged glass	No base	30"w x 26.5"d x 24.5"h
SM263024SWCGLNB	Left-hinged glass		
SM263024SWCSRNB	Right-hinged solid		
SM263024SWCSLNB	Left-hinged solid		
SM263458SWCGRM	Right-hinged glass	Mobile stand	34"w x 26"d x 58.75"h
SM263458SWCGLM	Left-hinged glass		
SM263458SWCSR	Right-hinged solid		
SM263458SWCSLM	Left-hinged solid		
SM263024SWCGRNBR	Right-hinged glass	Recessed (includes trim kit)	30"w x 26.5"d x 24.5"h
SM263024SWCGLNBR	Left-hinged glass		
SM263024SWCSRNB	Right-hinged solid		
SM263024SWCSLNB	Left-hinged solid		

Chamber I.D.

26"w x 23"d x 15.25"h
 5.27 Cubic Feet Storage
 Temperature Range
 90°-160° F (Tolerance +/- 1° F)

Electrical

120V, 6.3 Amp, 50/60 Hz,
 .45 kWh (Avg.),
 1535 BTU/hr (Avg.)

Interior Configuration

1 Adjustable Shelf



SM263024SWCGRNB
 No base (NB) standard for this model

Single Chamber Units

Product Number	Door Type	Base Type	Dimensions
SM263036SWCGR2B	Right-hinged glass	2" h base	30"w x 26.5"d x 36"h
SM263036SWCGL2B	Left-hinged glass		
SM263036SWCSR2B	Right-hinged solid		
SM263036SWCSL2B	Left-hinged solid		
SM263470SWCGRM	Right-hinged glass	Mobile stand	34"w x 26"d x 70.5"h
SM263470SWCGLM	Left-hinged glass		
SM263470SWCSR	Right-hinged solid		
SM263470SWCSLM	Left-hinged solid		
SM263036SWCGR2BR	Right-hinged glass	2" h base/recessed (includes trim kit)	30"w x 26.5"d x 36"h
SM263036SWCGL2BR	Left-hinged glass		
SM263036SWCSR2BR	Right-hinged solid		
SM263036SWCSL2BR	Left-hinged solid		

Chamber I.D.

26" w x 23" d x 25" h
 8.65 Cubic Feet Storage
 Temperature Range
 90°-160° F (Tolerance +/- 2° F)

Electrical

120V, 6.3 Amp, 50/60 Hz,
 .45 kWh (Avg.),
 1535 BTU/hr (Avg.)

Interior Configuration

2 Adjustable Shelves



SM263036SWCGR2B
 2" base (2B) standard for this model

Product Number	Door Type	Base Type	Dimensions
SM263074SWCGR4B	Right-hinged glass	4" h base	30"w x 26.5"d x 74.5"h
SM263074SWCGL4B	Left-hinged glass		
SM263074SWCSR4B	Right-hinged solid		
SM263074SWCSL4B	Left-hinged solid		
SM273181SWCGRM	Right-hinged glass	Mobile base	31"w x 27"d x 81.75"h
SM273181SWCGLM	Left-hinged glass		
SM273181SWCSR	Right-hinged solid		
SM273181SWCSLM	Left-hinged solid		
SM263074SWCGR4BR	Right-hinged glass	4" h base/recessed (includes trim kit)	30" w x 26.5" d x 74.5" h
SM263074SWCGL4BR	Left-hinged glass		
SM263074SWCSR4BR	Right-hinged solid		
SM263074SWCSL4BR	Left-hinged solid		

Chamber I.D.

26" w x 23" d x 61" h
 21.1 Cubic Feet Storage
 Temperature Range
 90°-160° F (Tolerance +/- 3° F)

Electrical

120V, 6.5 Amp, 50/60 Hz,
 .47 kWh (Avg.),
 1604 BTU/hr (Avg.)

Interior Configuration

2 Adjustable Shelves,
 1 Fixed Shelf



SM263074SWCGR4B
 4" base (4B) standard for this model

Dual Chamber Units

Product Number	Door Type	Base Type	Dimensions
SM263074DWCGR4B	Right-hinged glass	4" h base	30"w x 26.5"d x 74.5"h
SM263074DWCGL4B	Left-hinged glass		
SM263074DWCSR4B	Right-hinged solid		
SM263074DWCSL4B	Left-hinged solid		
SM273181DWCGRM	Right-hinged glass	Mobile base	31"w x 27"d x 81.75"h
SM273181DWCGLM	Left-hinged glass		
SM273181DWCSR4B	Right-hinged solid		
SM273181DWC4SLM	Left-hinged solid		
SM263074DWCGR4BR	Right-hinged glass	4" h base/recessed (includes trim kit)	30"w x 26.5"d x 74.5"h
SM263074DWCGL4BR	Left-hinged glass		
SM263074DWCSR4BR	Right-hinged solid		
SM263074DWCSL4BR	Left-hinged solid		

Upper Chamber I.D.

26"w x 23"d x 15.25"h
 5.28 Cubic Feet Storage
 Temperature Range
 90°-160° F (Tolerance +/- 1° F)

Lower Chamber I.D.

26"w x 23"W x 34.5"h
 11.93 Cubic Feet Storage
 Temperature Range
 90°-160° F (Tolerance +/- 3° F)

Electrical

120V, 12.5 Amp, 50/60 Hz,
 .90 kWh (Avg.),
 3071 BTU/hr (Avg.)

Interior Configuration

3 Adjustable Shelves



SM263074DWCGR4B
 4" base (4B) standard for this model

Accessories



Mobile Stand

Mobile stands are used with 24.5"h and 36"h warming cabinets to make them mobile. The stand adds 34" of height to the cabinet and includes a bottom shelf.



Mobile Base

Mobile bases are used with 74.5"h warming cabinets to make them mobile. The base adds 6.75" of height to the cabinet.